



SuperLink High-Gain Antenna

UACC-USL-ANT-HG



Overview

Dimensions	Device: 468.9 x 31.8 x 44.1 mm (18.5 x 1.3 x 1.7") With cable: 1458.4 x 31.8 x 44.1 mm (57.4 x 1.3 x 1.7") Cable: Ø5.2 x 1000 mm (Ø0.2 x 39.4")
Weatherproofing	IP67
Mounting	Pole mount
Pole Mount Diameter	1-2.17" (25-55 mm)
Wind Loading	25.4 N at 200 km/h (5.7 lbf at 125 mph)
UniFi Application Suite	Protect

Performance

Operating Frequency

- US 860–930 MHz
- EU 860–930 MHz
- Bluetooth 2400–2480 MHz

Antenna Gain

- Bluetooth 4 dBi
- SuperLink 7 dBi

Max. Range

- Bluetooth Up to 100 m (328 ft)
- SuperLink 5 km (3.1 mi)

Hardware

Weight	Device: 275 g (9.7 oz) Cable: 65 g (2.3 oz)
Enclosure Material	Polycarbonate, glass fiber
Mount Material	Stainless steel
Antenna Connector	(1) RP-N Female
Antenna Cable	(1) RP-SMA Male (1) RP-N Male
Ambient Operating Temperature	-40 to 60° C (-40 to 140° F)
Ambient Operating Humidity	10 to 90% noncondensing
Certifications	CE

For more information about this product or other Ubiquiti products, please visit: <https://techspecs.ui.com>

